HYBRID METHOD FOR MANUFACTURING TITANIUM COMPRESSOR IMPELLER

Patent number:

JP2004052754

Publication date:

2004-02-19

Inventor:

DECKER DAVID MICHAEL

Applicant:

BORG WARNER INC

Classification:

- international:

B22C7/02; B22C9/04; F04D29/02; F04D29/28; F04D29/30; B22C7/00; B22C9/04; F04D29/00; F04D29/28; F04D29/30; (IPC1-7): F04D29/28; B22C7/02; B22C9/04; B22C9/22; F04D29/02;

F04D29/30

- european:

B22C7/02; B22C9/04; F04D29/02C; F04D29/28C;

F04D29/30

Application number: JP20030131328 20030509 Priority number(s): US20020143150 20020510

Report a data error he

Also published as:


EP1361008 (A

US6588485 (B

Abstract of JP2004052754

PROBLEM TO BE SOLVED: To provide a simple, economical method for the mass production of titanium compressor wheels. SOLUTION: In a hybrid process, a wax pattern used in the investment casting process is intentionally designed not to produce a final (net shape) compressor impeller, but rather, is designed to produce a near net shape pattern including filled in areas which must be subsequently machined or milled away to produce the desired non-pullable shape compressor impeller. Surprisingly, when forming a titanium compressor impeller using the hybrid or two-step process, the technical complexity of each step (pattern forming and machining) is substantially lower, distortion of the wax blades during pattern casting is reduced, casting of titanium is simplified, the process allows itself to be fully automated, and the dimensional accuracy of the final product is greater than with conventional techniques.

COPYRIGHT: (C)2004,JPO



Data supplied from the esp@cenet database - Worldwide

REST AVAILABLE COPY